

# D130/230/430 series PRI Card Datasheet

## Features

- ▶ 1, 2, 4 T1/E1/J1 ports with PCI or PCI-E interface for high performance voice and data applications
- ▶ 32 bit bus master DMA data exchanges across PCI interface at 132 Mbytes/sec
- ▶ LEDs display the board's status
- ▶ Up to 30, 60, 120 Simultaneous voice calls respectively
- ▶ Scalable: Just adding more cards to extend the system
- ▶ Autosense compatibility with 5 V and 3.3 V PCI busses
- ▶ Worldwide usable: Configurable line interface to meet global telephone line interface requirements
- ▶ RoHS compliant
- ▶ Certificates: CE, FCC, A-Tick
- ▶ trixbox™ Officially Certified
- ▶ Elastix® Officially Certified

*Operating System*  
Linux (all versions, releases and distributions from 1.0 up)

## Requirements

- ▶ RAM 128 + MB Linux
- ▶ Kernel 2.4.X or 2.6.X
- ▶ CPU 800+ MHZ
- ▶ PCI or PCI-E slot

## Environments

- ▶ Temperature: 0 ~50°C (Operation)  
-40 ~125°C (Storage)
- ▶ Humidity: 10 ~90% NON-CONDENSING

## Overview

OpenVox D130/230/430 series PRI card is supposed to be the most advanced E1/T1/J1 Asterisk® card with superior quality in the open source community. The leading innovation ensures users to adjust the interrupts frequency to reduce the CPU load up to 70% and adjust the interrupt PIN to avoid interrupt sharing or conflict. E1, T1, J1 is selectable on per card or port basis, which enables signaling translation between E1 and T1 equipments and allows inexpensive T1 channel banks to connect with E1 circuits.

D130/230/430 series PRI card supports industry standard telephony and data protocols, including Primary Rate ISDN (both N. American and Standard Euro) protocol families for voice, PPP, Cisco, HDLC, and Frame Relay data modes. Both line-side and trunk-side interfaces are supported.

D130/230/430 cards work well with Asterisk®, Elastix®, FreeSWITCH™, PBX in a Flash, trixbox®, Yate™ and IPPBX/IVR projects as well as other Open Source and proprietary PBX, Switch, IVR, and VoIP gateway applications.

## Target Applications

- ▶ Voice-over Internet Protocol (VoIP) Services
- ▶ Complex IVR Trees
- ▶ "Meet-Me" Bridge Conferencing
- ▶ Calling Card Platforms
- ▶ VoIP Gateways (support SIP, H.323, and IAX)
- ▶ Legacy PBX/IVR Services
- ▶ Voice/Data Router (replace expensive routers)
- ▶ PRI/Switch Compatibility - Network or CPE

*3-Month "No Questions Asked" Return Policy  
Lifetime Warranty*

Pictures							
<b>Items</b>							
Products		D130P/DE130P	D130E/DE130E	D230P/DE230P	D230E/DE230E	D430P/DE430P	D430E/DE430E
Bus Type		PCI 2.2+	PCI-E 1.0+	PCI 2.2+	PCI-E 1.0+	PCI 2.2+	PCI-E 1.0+
Ports		1 RJ48	1 RJ48	2 RJ48	2 RJ48	4 RJ48	4 RJ48
Dimensions (mm)		120×64×16	120×68.5×16	120×64×16	120×68.5×16	120×64×16	120×68.5×16
Weights (g)		90/92	88/93	92/94	90/95	98/108	94/104
Optional EC Module		None/EC2032	None/EC2032	None/EC2064	None/EC2064	None/EC2128	None/EC2128
Bus Master DMA		✓	✓	✓	✓	✓	✓
Upgradable Firmware		✓	✓	✓	✓	✓	✓
Interrupt Frequency Modification		✓	✓	✓	✓	✓	✓
Interrupt PIN Selection		✓	✓	✓	✓	✓	✓
E1/T1	PRI	✓	✓	✓	✓	✓	✓
	SS1	✓	✓	✓	✓	✓	✓
	SS7	✓	✓	✓	✓	✓	✓